

KraftyBlok

Image Art

BEFORE YOU BEGIN

- Use ONLY LASER PRINTERS - Do not use an ink jet printer.
- Test with half sheets of copy paper to ensure images and print settings are properly set before loading Image Art paper.
- Reduce margins to the lowest setting.
- Not recommended for commercial grade printers or copiers. They become too hot and can melt the paper.
- If the machine is CAPABLE of printing in color, choose this option.
- Set printer for photo printing or best quality.

INSTRUCTIONS

Set document dimensions to 8.50" x 5.50" (landscape orientation) using any software which allows you to print images (for example: Word or Photoshop). Insert and adjust the desired images into the document. For the most economical use, fill the entire page before printing. Warm up the printer by running 5-6 plain sheets of paper through it.

Remove protective tissue from the Image Art paper. Insert the 8.50" x 5.50" paper into the printer tray. Select paper type glossy or photo paper. Follow printers instructions and print transfer. After printing allow the paper to set for 10-15 minutes before using. Trim the desired transfer to size and shape using scissors. Place the transfer into a bowl of water for approximately 1 minute for large color transfers or 30 seconds for smaller profiles.

Moisten the selected surface with water, where the Image Art transfer will be applied. Position Image Art transfer above the surface; then roll a ½" of the backing paper away from the top layer of the Image Art transfer (the decal). Line up the Image Art transfer on the surface. Take extra care when sliding larger images as they are a little more difficult to place due to their size.

Gently slide the Image Art transfer from the backing paper onto the surface using a finger to smooth the decal as you peel away the backing.

Please note, transfers are fragile and can tear easily, handle them carefully. Gently pat and smooth out the Image Art transfer with a moist paper towel eliminating air pockets and wrinkles.

Allow to dry overnight.

When dry, use a clear acrylic sealer specifically made for sealing decals and the surface on which you have applied the decal. Follow the manufacturer's directions when applying the sealer. When using a clear acrylic sealer on glass, mask off area around the decal to prevent sealer overspray.